

Notify the client of the updated engine oil fill volume.
Insert the updated chart in the client's owner's manual.

- This vehicle has received an updated engine oil fill volume and accompanying updated engine oil gauge (dipstick).
- Please follow the updated fluid capacity chart below for the correct engine oil fill volume for your vehicle.

CAPACITIES AND RECOMMENDED FLUIDS/LUBRICANTS

The following are approximate capacities. The actual refill capacities may be a little different. When refilling, follow the procedure instructed in the "8. Do-it-yourself" section to determine the proper refill capacity.

Fluid type	Capacity (approximate)	Recommended Fluids/Lubricants					
		Metric Measure	US Measure	Imperial Measure			
Fuel	76 L	20 gal	16-5/8 gal	· See "Fuel information (for VR30DDTT engine model)" (P.10-4) or "Fuel information (for 2.0L turbo gasoline engine model)" (P.10-6).			
Engine oil ¹ · Drain and refill · For additional information, see "Engine oil" (P.8-10).	VR30DDTT engine model	Two-Wheel Drive (2WD) model	With oil filter change	5.3 L	5-5/8 qt	4-5/8 qt	· Genuine "Nissan Motor Oil OW-20 SN" is recommended. · If the above motor oil is not available, use an equivalent motor oil that matches the above grade and viscosity. For additional information, see "Engine oil and oil filter recommendation" (P.10-8).
			Without oil filter change	5.1 L	5-3/8 qt	4-1/2 qt	
		All-Wheel Drive (AWD) model	With oil filter change	5.9 L	6-1/4 qt	5-1/4 qt	
			Without oil filter change	5.7 L	6 qt	5 qt	
		Two-Wheel Drive (2WD) model	With oil filter change	6.3 L	6-5/8 qt	5-1/2 qt	
			Without oil filter change	5.8 L	6-1/8 qt	5-1/8 qt	
	2.0L turbo gasoline engine model	All-Wheel Drive (AWD) model	With oil filter change	6.6 L	7 qt	5-7/8 qt	· Engine oil meeting specification MB229.5, viscosity SAE OW-30 or equivalent. · As an alternative to this recommended oil, engine oils meeting specification MB229.5, viscosity SAE OW-40, 5W-30 and 5W-40 may be used and meet oil specifications and requirements necessary to maintain the new vehicle limited warranty. · For additional information, refer to "Selecting the correct oil" (P.10-9) and "Oil viscosity" (P.10-9) under "Engine oil and oil filter recommendation" (P.10-8) of this manual.
			Without oil filter change	6.1 L	6-1/2 qt	5-3/8 qt	
		Total (with reservoir) Standard and premium grade		8.8 L	9-1/4 qt	7-3/4 qt	
		Total (with reservoir) Sport grade		10.3 L	10-7/8 qt	9-1/8 qt	
		Reservoir		0.6 L	5/8 qt	1/2 qt	
		Total (with reservoir)		9.0 L	9-1/2 qt	7-7/8 qt	
Engine coolant	VR30DDTT engine model	Reservoir		0.9 L	1 qt	3/4 qt	· BASF Glysant® G48® · Use BASF Glysant® G48® or equivalent in its system. Any damage to the vehicle or within the engine cooling system caused by the use of engine coolant other than as recommended is not covered under the INFINITI's new vehicle limited warranty.
		Total (with reservoir)		3.2 L	3-3/8 qt	2-7/8 qt	
Intercooler coolant	2.0L turbo gasoline engine model	Reservoir		0.4 L	3/8 qt	3/8 qt	· Pre-diluted Genuine NISSAN Long Life Antifreeze/Coolant (blue) or equivalent
		Total (with reservoir)					

10-2 Technical and consumer information

Figure 3