

TEQSPORT 5th GEN 4RUNNER DITCH LIGHT BRACKETS INSTALLATION MANUAL



This Installation Manual is intended for the following models:

2010-2024

Toyota 4Runner

PROLOGUE:

Study these instructions completely before proceeding to assembly. The installer must have a thorough knowledge of automotive systems operation. If unfamiliar with any of the concepts outlined in this instruction, we recommend the installation be completed by a qualified professional.

WARNING!

Extreme caution should be taken when performing maintenance or performance upgrades to your vehicle. Please observe and abide by any Warning or Caution labels placed on the various components and tools used when servicing your vehicle. If you have any questions regarding installation or the various components included with the TEQSPORT 5th Gen 4Runner Ditch Light Brackets, consult with a Professional Mechanic, or contact TEQSPORT for more information.

PARTS INCLUDED:

Item	Quantity	Description
1	1	Driver Side Bracket
2	1	Passenger Side Bracket

TOOLS REQUIRED:

- Ratchet
- Assorted Metric Sockets

SAFETY REQUIREMENTS:

- Always wear safety glasses and any necessary protective garments. If using any fluids, chemicals, or solvents, a respirator is recommended.
- Always turn the ignition to the OFF position and disconnect the NEGATIVE battery terminal.
- Always use properly rated jack stands when working under your vehicle.
- Always keep limbs and parts away from moving drivetrain parts.
- Only operate drivetrain in a safe space and well-ventilated areas.

BEFORE YOU BEGIN:

Remove contents from the TEQSPORT 5th Gen 4Runner Ditch Light Brackets and verify that ALL necessary hardware is present.

PROCEDURE:

1. Place the transmission in Park position (or in Reverse gear if equipped with a manual transmission). Apply the parking brake.
2. Open and support the hood of the vehicle.
3. Starting on the Driver Side of the vehicle, loosen but do not fully remove the (2) two bolts securing the Hood Hinge to the Hood. *Figure 1.*



Figure 1

4. Locate the Driver Side Ditch Light Bracket. Slide the Bracket between the Hood and the Hood Hinge as shown. *Figure 2.*



Figure 2

5. Retighten the (2) two OE Bolts to secure the Ditch Light Bracket.
6. Repeat *Steps 3-5* for the Passenger Side of the vehicle.
7. Attach desired Ditch Lights to the Brackets as shown. *Figure 3.*



Figure 3

END

Additional Technical Support:

Contact TEQSPORT at info@teqsport.com
Or call 770-832-7184 between 9am and 6pm ET